

856 Ship Notice/Manifest

Version: 1.0 Final

Company: ScanSource

Publication: 4/16/2018

Trading Partner: Customers

Notes:

Table of Contents

856	Ship Notice/Manifest	1
ISA	Interchange Control Header	3
GS	Functional Group Header	5
ST	Transaction Set Header	7
BSN	Beginning Segment for Ship Notice	8
DTM	Date/Time Reference	9
HL	Loop Hierarchical Level	10
HL	Hierarchical Level	11
LIN	Item Identification	12
SN1	Item Detail (Shipment)	14
PRF	Purchase Order Reference	15
PID	Product/Item Description	16
TD1	Carrier Details (Quantity and Weight)	17
TD5	Carrier Details (Routing Sequence/Transit Time)	18
REF	Reference Identification	19
MAN	Marks and Numbers	20
DTM	Date/Time Reference	21
N1	Loop Name	22
N1	Name	23
N2	Additional Name Information	24
N3	Address Information	25
N4	Geographic Location	26
CTT	Transaction Totals	27
SE	Transaction Set Trailer	28
GE	Functional Group Trailer	29
IEA	Interchange Control Trailer	30

856 Ship Notice/Manifest

Functional Group=SH

Not Defined:

<u>Page</u>	<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Notes</u>	<u>Usage</u>
3		ISA	Interchange Control Header	M	1			Must use
5		GS	Functional Group Header	M	1			Must use

Heading:

<u>Page</u>	<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Notes</u>	<u>Usage</u>
7	010	ST	Transaction Set Header	M	1			Must use
8	020	BSN	Beginning Segment for Ship Notice	M	1			Must use
9	040	DTM	Date/Time Reference	O	10			Used

Detail:

<u>Page</u>	<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Notes</u>	<u>Usage</u>
10	LOOP ID - HL					200000	C2/010L	
11	010	HL	Hierarchical Level	M	1			Must use
12	020	LIN	Item Identification	O	1			Used
14	030	SN1	Item Detail (Shipment)	O	1			Used
15	050	PRF	Purchase Order Reference	O	1			Used
16	070	PID	Product/Item Description	O	200			Used
17	110	TD1	Carrier Details (Quantity and Weight)	O	20			Used
18	120	TD5	Carrier Details (Routing Sequence/Transit Time)	O	12			Used
19	150	REF	Reference Identification	O	>1			Used
20	190	MAN	Marks and Numbers	O	>1			Used
21	200	DTM	Date/Time Reference	O	10			Used
22	LOOP ID - N1					200		
23	220	N1	Name	O	1			Used
24	230	N2	Additional Name Information	O	2			Used
25	240	N3	Address Information	O	2			Used
26	250	N4	Geographic Location	O	1			Used

Summary:

<u>Page</u>	<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Notes</u>	<u>Usage</u>
27	010	CTT	Transaction Totals	O	1		N3/010	Used
28	020	SE	Transaction Set Trailer	M	1			Must use

Not Defined:

<u>Page</u>	<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Notes</u>	<u>Usage</u>
29		GE	Functional Group Trailer	M	1			Must use

<u>Page</u>	<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Notes</u>	<u>Usage</u>
30		IEA	Interchange Control Trailer	M	1			Must use

Notes:

3/010 Number of line items (CTT01) is the accumulation of the number of HL segments. If used, hash total (CTT02) is the sum of the value of units shipped (SN102) for each SN1 segment.

Comments:

2/010L The HL segment is the only mandatory segment within the HL loop, and by itself, the HL segment has no meaning.

ISA Interchange Control Header

Pos:	Max: 1
Not Defined - Mandatory	
Loop: N/A	Elements: 16

User Option (Usage): Must use

Purpose: To start and identify an interchange of zero or more functional groups and interchange-related control segments

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
ISA01	I01	Authorization Information Qualifier	M	ID	2/2	Must use

Description: Code to identify the type of information in the Authorization Information
All valid standard codes are used.

ISA02	I02	Authorization Information	M	AN	10/10	Must use
-------	-----	----------------------------------	---	----	-------	----------

Description: Information used for additional identification or authorization of the interchange sender or the data in the interchange; the type of information is set by the Authorization Information Qualifier (I01)

ISA03	I03	Security Information Qualifier	M	ID	2/2	Must use
-------	-----	---------------------------------------	---	----	-----	----------

Description: Code to identify the type of information in the Security Information
All valid standard codes are used.

ISA04	I04	Security Information	M	AN	10/10	Must use
-------	-----	-----------------------------	---	----	-------	----------

Description: This is used for identifying the security information about the interchange sender or the data in the interchange; the type of information is set by the Security Information Qualifier (I03)

ISA05	I05	Interchange ID Qualifier	M	ID	2/2	Must use
-------	-----	---------------------------------	---	----	-----	----------

Description: Qualifier to designate the system/method of code structure used to designate the sender or receiver ID element being qualified

Code Name

12	Phone (Telephone Companies)
ZZ	Mutually Defined

ISA06	I06	Interchange Sender ID	M	AN	15/15	Must use
-------	-----	------------------------------	---	----	-------	----------

Description: Identification code published by the sender for other parties to use as the receiver ID to route data to them; the sender always codes this value in the sender ID element

User Note 1:

SCANSOURCE NA:	8642882432
SCANSOURCE EU:	8009155550
SCANSOURCE LA:	3053984000
TEST:	8643298222

ISA07	I05	Interchange ID Qualifier	M	ID	2/2	Must use
-------	-----	---------------------------------	---	----	-----	----------

Description: Qualifier to designate the system/method of code structure used to designate the sender or receiver ID element being qualified

All valid standard codes are used.

ISA08	I07	Interchange Receiver ID	M	AN	15/15	Must use
-------	-----	--------------------------------	---	----	-------	----------

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
		Description: Identification code published by the receiver of the data; When sending, it is used by the sender as their sending ID, thus other parties sending to them will use this as a receiving ID to route data to them				
ISA09	I08	Interchange Date	M	DT	6/6	Must use
		Description: Date of the interchange				
ISA10	I09	Interchange Time	M	TM	4/4	Must use
		Description: Time of the interchange				
ISA11	I10	Interchange Control Standards Identifier	M	ID	1/1	Must use
		Description: Code to identify the agency responsible for the control standard used by the message that is enclosed by the interchange header and trailer All valid standard codes are used.				
ISA12	I11	Interchange Control Version Number	M	ID	5/5	Must use
		Description: Code specifying the version number of the interchange control segments All valid standard codes are used.				
ISA13	I12	Interchange Control Number	M	N0	9/9	Must use
		Description: A control number assigned by the interchange sender				
ISA14	I13	Acknowledgment Requested	M	ID	1/1	Must use
		Description: Code sent by the sender to request an interchange acknowledgment (TA1) All valid standard codes are used.				
ISA15	I14	Usage Indicator	M	ID	1/1	Must use
		Description: Code to indicate whether data enclosed by this interchange envelope is test, production or information				
		Code Name				
		P Production Data				
		T Test Data				
ISA16	I15	Component Element Separator	M		1/1	Must use
		Description: Type is not applicable; the component element separator is a delimiter and not a data element; this field provides the delimiter used to separate component data elements within a composite data structure; this value must be different than the data element separator and the segment terminator				

GS Functional Group Header

Pos:	Max: 1
Not Defined - Mandatory	
Loop: N/A	Elements: 8

User Option (Usage): Must use

Purpose: To indicate the beginning of a functional group and to provide control information

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
GS01	479	Functional Identifier Code	M	ID	2/2	Must use

Description: Code identifying a group of application related transaction sets

Code Name

SH Ship Notice/Manifest (856)

GS02	142	Application Sender's Code	M	AN	2/15	Must use
------	-----	----------------------------------	---	----	------	----------

Description: Code identifying party sending transmission; codes agreed to by trading partners

User Note 1: See Codes in ISA08

GS03	124	Application Receiver's Code	M	AN	2/15	Must use
------	-----	------------------------------------	---	----	------	----------

Description: Code identifying party receiving transmission; codes agreed to by trading partners

GS04	373	Date	M	DT	8/8	Must use
------	-----	-------------	---	----	-----	----------

Description: Date expressed as CCYYMMDD

GS05	337	Time	M	TM	4/8	Must use
------	-----	-------------	---	----	-----	----------

Description: Time expressed in 24-hour clock time as follows: HHMM, or HHMMSS, or HHMMSSD, or HHMMSSDD, where H = hours (00-23), M = minutes (00-59), S = integer seconds (00-59) and DD = decimal seconds; decimal seconds are expressed as follows: D = tenths (0-9) and DD = hundredths (00-99)

GS06	28	Group Control Number	M	N0	1/9	Must use
------	----	-----------------------------	---	----	-----	----------

Description: Assigned number originated and maintained by the sender

GS07	455	Responsible Agency Code	M	ID	1/2	Must use
------	-----	--------------------------------	---	----	-----	----------

Description: Code identifying the issuer of the standard; this code is used in conjunction with Data Element 480

All valid standard codes are used.

GS08	480	Version / Release / Industry Identifier Code	M	AN	1/12	Must use
------	-----	---	---	----	------	----------

Description: Code indicating the version, release, subrelease, and industry identifier of the EDI standard being used, including the GS and GE segments; if code in DE455 in GS segment is X, then in DE 480 positions 1-3 are the version number; positions 4-6 are the release and subrelease, level of the version; and positions 7-12 are the industry or trade association identifiers (optionally assigned by user); if code in DE455 in GS segment is T, then other formats are allowed

Code Name

004010 Draft Standards Approved for Publication by ASC X12 Procedures Review Board through October 1997

Semantics:

1. GS04 is the group date.
2. GS05 is the group time.
3. The data interchange control number GS06 in this header must be identical to the same data element in the associated functional group trailer, GE02.

Comments:

1. A functional group of related transaction sets, within the scope of X12 standards, consists of a collection of similar transaction sets enclosed by a functional group header and a functional group trailer.

ST Transaction Set Header

Pos: 010	Max: 1
Heading - Mandatory	
Loop: N/A	Elements: 2

User Option (Usage): Must use

Purpose: To indicate the start of a transaction set and to assign a control number

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
ST01	143	Transaction Set Identifier Code	M	ID	3/3	Must use

Description: Code uniquely identifying a Transaction Set

Code Name

856 Ship Notice/Manifest

ST02	329	Transaction Set Control Number	M	AN	4/9	Must use
------	-----	--------------------------------	---	----	-----	----------

Description: Identifying control number that must be unique within the transaction set functional group assigned by the originator for a transaction set

Semantics:

1. The transaction set identifier (ST01) used by the translation routines of the interchange partners to select the appropriate transaction set definition (e.g., 810 selects the Invoice Transaction Set).

BSN Beginning Segment for Ship Notice

Pos: 020	Max: 1
Heading - Mandatory	
Loop: N/A	Elements: 4

User Option (Usage): Must use

Purpose: To transmit identifying numbers, dates, and other basic data relating to the transaction set

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
BSN01	353	Transaction Set Purpose Code	M	ID	2/2	Must use
		Description: Code identifying purpose of transaction set				
		Code Name				
		00		Original		
BSN02	396	Shipment Identification	M	AN	2/30	Must use
		Description: A unique control number assigned by the original shipper to identify a specific shipment				
BSN03	373	Date	M	DT	8/8	Must use
		Description: Date expressed as CCYYMMDD				
BSN04	337	Time	O	TM	4/8	Used
		Description: Time expressed in 24-hour clock time as follows: HHMM, or HHMMSS, or HHMMSSD, or HHMMSSDD, where H = hours (00-23), M = minutes (00-59), S = integer seconds (00-59) and DD = decimal seconds; decimal seconds are expressed as follows: D = tenths (0-9) and DD = hundredths (00-99)				

Semantics:

1. BSN03 is the date the shipment transaction set is created.
2. BSN04 is the time the shipment transaction set is created.

Comments:

- 1.

DTM Date/Time Reference

Pos: 040	Max: 10
Heading - Optional	
Loop: N/A	Elements: 4

User Option (Usage): Used

Purpose: To specify pertinent dates and times

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
DTM01	374	Date/Time Qualifier	M	ID	3/3	Must use
Description: Code specifying type of date or time, or both date and time						
Code Name						
011 Shipped						
DTM02	373	Date	X	DT	8/8	Used
Description: Date expressed as CCYYMMDD						
DTM03	337	Time	X	TM	4/8	Used
Description: Time expressed in 24-hour clock time as follows: HHMM, or HHMMSS, or HHMMSSD, or HHMMSSDD, where H = hours (00-23), M = minutes (00-59), S = integer seconds (00-59) and DD = decimal seconds; decimal seconds are expressed as follows: D = tenths (0-9) and DD = hundredths (00-99)						
DTM04	623	Time Code	O	ID	2/2	Used
Description: Code identifying the time. In accordance with International Standards Organization standard 8601, time can be specified by a + or - and an indication in hours in relation to Universal Time Coordinate (UTC) time; since + is a restricted character, + and - are substituted by P and M in the codes that follow						
All valid standard codes are used.						

Syntax Rules:

1. R020305 - At least one of DTM02, DTM03 or DTM05 is required.
2. C0403 - If DTM04 is present, then DTM03 is required.

Loop Hierarchical Level

Pos: 010	Repeat: 200000
Mandatory	
Loop: HL	Elements: N/A

User Option (Usage): Must use

Purpose: To identify dependencies among and the content of hierarchically related groups of data segments

Loop Summary:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Usage</u>
010	HL	Hierarchical Level	M	1		Must use
020	LIN	Item Identification	O	1		Used
030	SN1	Item Detail (Shipment)	O	1		Used
050	PRF	Purchase Order Reference	O	1		Used
070	PID	Product/Item Description	O	200		Used
110	TD1	Carrier Details (Quantity and Weight)	O	20		Used
120	TD5	Carrier Details (Routing Sequence/Transit Time)	O	12		Used
150	REF	Reference Identification	O	>1		Used
190	MAN	Marks and Numbers	O	>1		Used
200	DTM	Date/Time Reference	O	10		Used
220		Loop N1	O		200	Used

HL Hierarchical Level

Pos: 010	Max: 1
Detail - Mandatory	
Loop: HL	Elements: 3

User Option (Usage): Must use

Purpose: To identify dependencies among and the content of hierarchically related groups of data segments

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
HL01	628	Hierarchical ID Number	M	AN	1/12	Must use
Description: A unique number assigned by the sender to identify a particular data segment in a hierarchical structure						
HL02	734	Hierarchical Parent ID Number	O	AN	1/12	Used
Description: Identification number of the next higher hierarchical data segment that the data segment being described is subordinate to						
HL03	735	Hierarchical Level Code	M	ID	1/2	Must use
Description: Code defining the characteristic of a level in a hierarchical structure						
Code Name						
I Item						
O Order						
P Pack						
S Shipment						

Comments:

1. The HL segment is used to identify levels of detail information using a hierarchical structure, such as relating line-item data to shipment data, and packaging data to line-item data.
2. The HL segment defines a top-down/left-right ordered structure.
3. HL01 shall contain a unique alphanumeric number for each occurrence of the HL segment in the transaction set. For example, HL01 could be used to indicate the number of occurrences of the HL segment, in which case the value of HL01 would be "1" for the initial HL segment and would be incremented by one in each subsequent HL segment within the transaction.
4. HL02 identifies the hierarchical ID number of the HL segment to which the current HL segment is subordinate.
5. HL03 indicates the context of the series of segments following the current HL segment up to the next occurrence of an HL segment in the transaction. For example, HL03 is used to indicate that subsequent segments in the HL loop form a logical grouping of data referring to shipment, order, or item-level information.
6. HL04 indicates whether or not there are subordinate (or child) HL segments related to the current HL segment.

LIN Item Identification

Pos: 020	Max: 1
Detail - Optional	
Loop: HL	Elements: 7

User Option (Usage): Used

Purpose: To specify basic item identification data

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
LIN01	350	Assigned Identification	O	AN	1/20	Used
		Description: Alphanumeric characters assigned for differentiation within a transaction set				
LIN02	235	Product/Service ID Qualifier	M	ID	2/2	Must use
		Description: Code identifying the type/source of the descriptive number used in Product/Service ID (234)				
		Code Name				
		BP Buyer's Part Number				
LIN03	234	Product/Service ID	M	AN	1/48	Must use
		Description: Identifying number for a product or service				
LIN04	235	Product/Service ID Qualifier	X	ID	2/2	Used
		Description: Code identifying the type/source of the descriptive number used in Product/Service ID (234)				
		Code Name				
		VP Vendor's (Seller's) Part Number				
LIN05	234	Product/Service ID	X	AN	1/48	Used
		Description: Identifying number for a product or service				
LIN06	235	Product/Service ID Qualifier	X	ID	2/2	Used
		Description: Code identifying the type/source of the descriptive number used in Product/Service ID (234)				
		Code Name				
		MG Manufacturer's Part Number				
LIN07	234	Product/Service ID	X	AN	1/48	Used
		Description: Identifying number for a product or service				

Syntax Rules:

1. P0405 - If either LIN04 or LIN05 is present, then the other is required.
2. P0607 - If either LIN06 or LIN07 is present, then the other is required.

Semantics:

- 1.

Comments:

1.

User Note 1:

This sement is used if HL03 = 'I'

SN1 Item Detail (Shipment)

Pos: 030	Max: 1
Detail - Optional	
Loop: HL	Elements: 5

User Option (Usage): Used

Purpose: To specify line-item detail relative to shipment

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
SN101	350	Assigned Identification	O	AN	1/20	Used
		Description: Alphanumeric characters assigned for differentiation within a transaction set				
SN102	382	Number of Units Shipped	M	R	1/10	Must use
		Description: Numeric value of units shipped in manufacturer's shipping units for a line item or transaction set				
SN103	355	Unit or Basis for Measurement Code	M	ID	2/2	Must use
		Description: Code specifying the units in which a value is being expressed, or manner in which a measurement has been taken				
		All valid standard codes are used.				
SN105	330	Quantity Ordered	X	R	1/15	Used
		Description: Quantity ordered				
SN106	355	Unit or Basis for Measurement Code	X	ID	2/2	Used
		Description: Code specifying the units in which a value is being expressed, or manner in which a measurement has been taken				
		All valid standard codes are used.				

Syntax Rules:

1. P0506 - If either SN105 or SN106 is present, then the other is required.

Semantics:

- 1.

Comments:

- 1.

PRF Purchase Order Reference

Pos: 050	Max: 1
Detail - Optional	
Loop: HL	Elements: 2

User Option (Usage): Used

Purpose: To provide reference to a specific purchase order

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
PRF01	324	Purchase Order Number	M	AN	1/22	Must use
		Description: Identifying number for Purchase Order assigned by the orderer/purchaser				
PRF04	373	Date	O	DT	8/8	Used
		Description: Date expressed as CCYYMMDD				

Semantics:

1. PRF04 is the date assigned by the purchaser to purchase order.

PID Product/Item Description

Pos: 070	Max: 200
Detail - Optional	
Loop: HL	Elements: 2

User Option (Usage): Used

Purpose: To describe a product or process in coded or free-form format

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
PID01	349	Item Description Type	M	ID	1/1	Must use

Description: Code indicating the format of a description

Code Name

F Free-form

PID05	352	Description	X	AN	1/80	Used
-------	-----	-------------	---	----	------	------

Description: A free-form description to clarify the related data elements and their content

Semantics:

- 1.

TD1 Carrier Details (Quantity and Weight)

Pos: 110	Max: 20
Detail - Optional	
Loop: HL	Elements: 5

User Option (Usage): Used

Purpose: To specify the transportation details relative to commodity, weight, and quantity

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
TD101	103	Packaging Code	O	AN	3/5	Used
		Description: Code identifying the type of packaging; Part 1: Packaging Form, Part 2: Packaging Material; if the Data Element is used, then Part 1 is always required All valid standard codes are used.				
TD102	80	Lading Quantity	X	N0	1/7	Used
		Description: Number of units (pieces) of the lading commodity				
TD106	187	Weight Qualifier	O	ID	1/2	Used
		Description: Code defining the type of weight				
		<u>Code</u> <u>Name</u>				
		G Gross Weight				
TD107	81	Weight	X	R	1/10	Used
		Description: Numeric value of weight				
TD108	355	Unit or Basis for Measurement Code	X	ID	2/2	Used
		Description: Code specifying the units in which a value is being expressed, or manner in which a measurement has been taken All valid standard codes are used.				

Syntax Rules:

1. C0102 - If TD101 is present, then TD102 is required.
2. C0607 - If TD106 is present, then TD107 is required.
3. P0708 - If either TD107 or TD108 is present, then the other is required.

TD5 Carrier Details (Routing Sequence/Transit Time)

Pos: 120	Max: 12
Detail - Optional	
Loop: HL	Elements: 5

User Option (Usage): Used

Purpose: To specify the carrier and sequence of routing and provide transit time information

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
TD501	133	Routing Sequence Code	O	ID	1/2	Used

Description: Code describing the relationship of a carrier to a specific shipment movement

Code Name

B Origin/Delivery Carrier (Any Mode)
O Origin Carrier (Air, Motor, or Ocean)

TD502	66	Identification Code Qualifier	X	ID	1/2	Used
-------	----	-------------------------------	---	----	-----	------

Description: Code designating the system/method of code structure used for Identification Code (67)

All valid standard codes are used.

TD503	67	Identification Code	X	AN	2/80	Used
-------	----	---------------------	---	----	------	------

Description: Code identifying a party or other code

TD504	91	Transportation Method/Type Code	X	ID	1/2	Used
-------	----	---------------------------------	---	----	-----	------

Description: Code specifying the method or type of transportation for the shipment

All valid standard codes are used.

TD505	387	Routing	X	AN	1/35	Used
-------	-----	---------	---	----	------	------

Description: Free-form description of the routing or requested routing for shipment, or the originating carrier's identity

Syntax Rules:

1. R0204050612 - At least one of TD502, TD504, TD505, TD506 or TD512 is required.
2. C0203 - If TD502 is present, then TD503 is required.

Semantics:

- 1.

Comments:

- 1.

REF Reference Identification

Pos: 150	Max: >1
Detail - Optional	
Loop: HL	Elements: 2

User Option (Usage): Used

Purpose: To specify identifying information

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
REF01	128	Reference Identification Qualifier	M	ID	2/3	Must use

Description: Code qualifying the Reference Identification

Code Name

SE Serial Number

REF02	127	Reference Identification	X	AN	1/30	Used
-------	-----	--------------------------	---	----	------	------

Description: Reference information as defined for a particular Transaction Set or as specified by the Reference Identification Qualifier

Syntax Rules:

1. R0203 - At least one of REF02 or REF03 is required.

Semantics:

- 1.

MAN Marks and Numbers

Pos: 190	Max: >1
Detail - Optional	
Loop: HL	Elements: 2

User Option (Usage): Used

Purpose: To indicate identifying marks and numbers for shipping containers

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
MAN01	88	Marks and Numbers Qualifier	M	ID	1/2	Must use
		Description: Code specifying the application or source of Marks and Numbers (87) All valid standard codes are used.				
MAN02	87	Marks and Numbers	M	AN	1/48	Must use
		Description: Marks and numbers used to identify a shipment or parts of a shipment				

Semantics:

1. MAN01/MAN02 and MAN04/MAN05 may be used to identify two different marks and numbers assigned to the same physical container.

DTM Date/Time Reference

Pos: 200	Max: 10
Detail - Optional	
Loop: HL	Elements: 3

User Option (Usage): Used

Purpose: To specify pertinent dates and times

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
DTM01	374	Date/Time Qualifier	M	ID	3/3	Must use
		Description: Code specifying type of date or time, or both date and time All valid standard codes are used.				
DTM02	373	Date	X	DT	8/8	Used
		Description: Date expressed as CCYYMMDD				
DTM03	337	Time	X	TM	4/8	Used
		Description: Time expressed in 24-hour clock time as follows: HHMM, or HHMMSS, or HHMMSSD, or HHMMSSDD, where H = hours (00-23), M = minutes (00-59), S = integer seconds (00-59) and DD = decimal seconds; decimal seconds are expressed as follows: D = tenths (0-9) and DD = hundredths (00-99)				

Syntax Rules:

1. R020305 - At least one of DTM02, DTM03 or DTM05 is required.

Loop Name

Pos: 220	Repeat: 200
Optional	
Loop: N1	Elements: N/A

User Option (Usage): Used

Purpose: To identify a party by type of organization, name, and code

Loop Summary:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Usage</u>
220	N1	Name	O	1		Used
230	N2	Additional Name Information	O	2		Used
240	N3	Address Information	O	2		Used
250	N4	Geographic Location	O	1		Used

N1 Name

Pos: 220	Max: 1
Detail - Optional	
Loop: N1	Elements: 2

User Option (Usage): Used

Purpose: To identify a party by type of organization, name, and code

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
N101	98	Entity Identifier Code	M	ID	2/3	Must use

Description: Code identifying an organizational entity, a physical location, property or an individual

Code Name

SF Ship From
ST Ship To

N102	93	Name	X	AN	1/40	Used
------	----	-------------	---	----	------	------

Description: Free-form name

Syntax Rules:

1. R0203 - At least one of N102 or N103 is required.

Comments:

1. This segment, used alone, provides the most efficient method of providing organizational identification. To obtain this efficiency the "ID Code" (N104) must provide a key to the table maintained by the transaction processing party.

N2 Additional Name Information

Pos: 230	Max: 2
Detail - Optional	
Loop: N1	Elements: 1

User Option (Usage): Used

Purpose: To specify additional names or those longer than 35 characters in length

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
N201	93	Name	M	AN	1/40	Must use

Description: Free-form name

N3 Address Information

Pos: 240	Max: 2
Detail - Optional	
Loop: N1	Elements: 2

User Option (Usage): Used

Purpose: To specify the location of the named party

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
N301	166	Address Information	M	AN	1/40	Must use
		Description: Address information				
N302	166	Address Information	O	AN	1/40	Used
		Description: Address information				

N4 Geographic Location

Pos: 250	Max: 1
Detail - Optional	
Loop: N1	Elements: 4

User Option (Usage): Used

Purpose: To specify the geographic place of the named party

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
N401	19	City Name	O	AN	2/30	Used
		Description: Free-form text for city name				
N402	156	State or Province Code	O	ID	2/2	Used
		Description: Code (Standard State/Province) as defined by appropriate government agency				
N403	116	Postal Code	O	ID	3/15	Used
		Description: Code defining international postal zone code excluding punctuation and blanks (zip code for United States)				
N404	26	Country Code	O	ID	2/3	Used
		Description: Code identifying the country				

CTT Transaction Totals

Pos: 010	Max: 1
Summary - Optional	
Loop: N/A	Elements: 1

User Option (Usage): Used

Purpose: To transmit a hash total for a specific element in the transaction set

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
CTT01	354	Number of Line Items	M	NO	1/6	Must use

Description: Total number of line items in the transaction set

Comments:

1. This segment is intended to provide hash totals to validate transaction completeness and correctness.

SE Transaction Set Trailer

Pos: 020	Max: 1
Summary - Mandatory	
Loop: N/A	Elements: 2

User Option (Usage): Must use

Purpose: To indicate the end of the transaction set and provide the count of the transmitted segments (including the beginning (ST) and ending (SE) segments)

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
SE01	96	Number of Included Segments	M	N0	1/10	Must use
		Description: Total number of segments included in a transaction set including ST and SE segments				
SE02	329	Transaction Set Control Number	M	AN	4/9	Must use
		Description: Identifying control number that must be unique within the transaction set functional group assigned by the originator for a transaction set				

Comments:

1. SE is the last segment of each transaction set.

GE Functional Group Trailer

Pos:	Max: 1
Not Defined - Mandatory	
Loop: N/A	Elements: 2

User Option (Usage): Must use

Purpose: To indicate the end of a functional group and to provide control information

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
GE01	97	Number of Transaction Sets Included	M	N0	1/6	Must use
		Description: Total number of transaction sets included in the functional group or interchange (transmission) group terminated by the trailer containing this data element				
GE02	28	Group Control Number	M	N0	1/9	Must use
		Description: Assigned number originated and maintained by the sender				

Semantics:

1. The data interchange control number GE02 in this trailer must be identical to the same data element in the associated functional group header, GS06.

Comments:

1. The use of identical data interchange control numbers in the associated functional group header and trailer is designed to maximize functional group integrity. The control number is the same as that used in the corresponding header.

IEA Interchange Control Trailer

Pos:	Max: 1
Not Defined - Mandatory	
Loop: N/A	Elements: 2

User Option (Usage): Must use

Purpose: To define the end of an interchange of zero or more functional groups and interchange-related control segments

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
IEA01	I16	Number of Included Functional Groups	M	N0	1/5	Must use
		Description: A count of the number of functional groups included in an interchange				
IEA02	I12	Interchange Control Number	M	N0	9/9	Must use
		Description: A control number assigned by the interchange sender				